TCP/IP Setup Utility Manual

Thermal Printer

Receipt Printer

Rev. 2.11

Table of Contents

- 1. Explanation.
- 2. How to use.
 - 2.1 TCP/IP Configuration.
 - 2.2 Ethernet firmware update.

1. Explanation.

This TCP/IP Setup Utility Manual shows how to find the printer which is connected to the network and set the TCP/IP information of the printer.

2. How to use.

2.1 TCP/IP configuration.

Execute the TCPIPConfig.exe file.

Ethernet(TCP/IP) Configuration Utility 2.00	×
Searching printers 44 A8 C2 Read Search using MAC Address	Search
	F/W Update
F/W Version : IP Address :	IP : Open Firmware Update File Name : Firmware Update
10.2 Save Test print	Exit

Click the "Search" button.

📸 Ethernet(TCP/IP) Configuration Utility 2.00	×
Searching printers 44 A8 C2 Read Search using MAC Address Ethernet Printer Searching	Search
Now searching printers 44:A	
Port : 9100	
Save Test print	Exit

Two printer types(ATMEL & STM CPU) support different UI.

So choose the printer type on the left and enter the setup information on the right of the utility.

After entering setup information, click "Save" button.

<ATMEL CPU> [MAC Address : 00:30:F9:XX:XX]

IP Address :					
00:30:F9:09:80:33	192 . 168 . 1 . 104				
44:A8:C2:00:00:02	SUBNET MASK :				
	255 . 255 . 255 . 0				
	Gateway :				
	192 . 168 . 1 . 1				
	Port : 9100				
10.2	Test print				

<STM CPU> [MAC Address : 44:A8:C2:XX:XX]

Ethernet printer's Information		F/W Update ——
FAW Version : 2.05	IP Address : 192 . 168 . 1 . 100	IP: 192.168.1.100
44:A8:C2:00:00:02	SUBNET MASK : 255 . 255 . 255 . 0	Open Firmware
	Gateway :	Update File Name :
	192 . 168 . 1 . 1	
	Port : 9000	Firmware Update
	DHCP Setting(Use DHCP)	
Save	Test print	Exit

When you see the dialog message as below, click "OK" button.

Printer Settings Saved		×
	Save Completed !!!	
	∂ 100 OK	

2.2 Ethernet Firmware update.

Click "Open Firmware" button."

🖥 Ethernet(TCP/IP) (Configuration Utility 2.00	X
Searching printers – 44 A8 C2	Read Address	Search
Ethernet	printer's Information	F/W Update
FAW Version : 2.05	IP Address : 192 . 168 . 1 . 100	IP: 192.168.1.100
44:A8:C2:00:00:02	SUBNET MASK : 255 . 255 . 255 . 0	Open Firmware
	Gateway :	Update File Name :
	192 . 168 . 1 . 1 Port : 9000	Firmware Update
10.2 Save	Test print	Exit

Choose the firmware which you want to upload and click "Open" Button.

열기							? 🗙
찾는 위치(!):	🚞 Ethernet firmware	~	G	ø	Þ	•	
BR LKEther_v204.b							
<mark>LKEther_v205,b</mark>							
파일 이름(<u>N</u>):	LKEther_v205, bin				L	열기	0
파일 형식(<u>T</u>):	Binary File (*,bin)		~			취	소

Click Firmware Update" Button and when the firmware uploading is completed you could see the below dialog message.

Click "OK" Button..

Firmware downloading is completed,	×
Firmware downloading is completed. Please turn off the printer and turn it on again.	
ок	